

OCEANAIRE

MODEL: 2OACH1811

1.5 TON PORTABLE HEAT PUMP

TECHNICAL SPECIFICATIONS

COOLING CAPACITY	16,800 BTUH
HEATING CAPACITY	15,600 BTUH
VOLTAGE	115 V, 60 Hz, Single Phase
AMPS	14.1 A
WATTS	1670 W
IN RUSH AMPS	75 A
EER	10.0
COMPRESSOR TYPE	ROTARY
COMPRESSOR MOTOR	1-1/2 HP
COMPRESSOR RLA	12.3 A
COMPRESSOR LRA	63 A
EVAPORATOR BLOWER	CENTRIFUGAL
EVAP CFM - HIGH	600
EVAP MOTOR HP	1/8 HP
CONDENSER BLOWER	CENTRIFUGAL
COND CFM	930
COND MOTOR HP	1/8 HP
POWER CORD	14/3
PLUG TYPE	5-20P, LCDI
CORD LENGTH	10 FT
CONDENSATE REMOVAL	TANK
SIZE	5 GALLON
REFRIGERANT CHARGE	40 OZ., R-410A
HEIGHT W/ CASTERS	45-3/4 in
HEIGHT W/O CASTERS	40-1/2 in
WIDTH	24 in
DEPTH	30 in
NET WEIGHT	260 lb.



HEATING & COOLING



WARRANTY

ALL OCEANAIRE PRODUCTS ARE COVERED BY THE OCEANAIRE LIMITED WARRANTY

1 YEAR ON THE FULL PRODUCT PLUS, 4 ADDITIONAL YEARS FOR THE COMPRESSOR (RESTRICTIONS APPLY)

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

- OA **Cooling Capacity** is total BTUH at 80°DB/67°WB return air, 95°F Outdoor at high fan speed
- OA **Heating Capacity** is total BTUH at 70°DB/60°WB indoor, 47°DB/43°WB Outdoor
- OA Dedicated Circuit and Time Delay fuses/circuit breakers are recommended
- OA EER is determined at high fan speed, with condenser discharge air ducted into another area
- OA CFM with free discharge
- OA Amps & Watts at 115 Volts

COOLING AMBIENT OPERATING RANGE 65° TO 105°

HEATING AMBIENT OPERATING RANGE 40° TO 85°

NOT APPROVED FOR OUTDOOR USE




OA-TS-2OACH1811-07262018

OCEANAIRE
OCEANAIRE-INC.COM



FEATURES:

- OA SOLID STATE ELECTRONIC CONTROLLER WITH AUTOMATIC MODE CHANGEOVER
- OA AUTOMATIC 6-SPEED FAN CONTROL WITH MANUAL OVERRIDE
- OA LARGE LED DISPLAY
- OA SWIVEL BALL BEARING CASTERS WITH LOCKS AT FRONT
- OA CONDENSATE TANK ALERT
- OA LCDI POWER CORD
- OA HIGH PRESSURE SAFETY SWITCH
- OA WASHABLE ELECTROSTATIC AIR FILTERS



ACCESSORIES

