

OCEANAIRE

MODEL: 2OAC1211
1 TON DELUXE SPOT COOLER

TECHNICAL SPECIFICATIONS

COOLING CAPACITY	11,800 BTUH
VOLTAGE	115 V, 60 Hz, Single Phase
AMPS	10.4 A
WATTS	1180 W
IN RUSH AMPS	60 A
EER	10.0
COMPRESSOR TYPE	ROTARY
COMPRESSOR MOTOR	1 HP
COMPRESSOR RLA	9.5 A
COMPRESSOR LRA	50 A
EVAPORATOR BLOWER	CENTRIFUGAL
EVAP CFM - HIGH	400
EVAP MOTOR HP	1/8 HP
CONDENSER BLOWER	CENTRIFUGAL
COND CFM	580
COND MOTOR HP	1/8 HP
POWER CORD	14/3
PLUG TYPE	5-15P, LCDI
CORD LENGTH	10 FT
CONDENSATE REMOVAL SIZE	TANK 5 GALLON
REFRIGERANT CHARGE	18 OZ., R-410A
HEIGHT W/ CASTERS	37-3/4 in
HEIGHT W/O CASTERS	32-1/2 in
WIDTH	20 in
DEPTH	25 in
NET WEIGHT	180 lb.



AIR COOLED



WARRANTY

ALL OCEANAIRE PRODUCTS ARE COVERED BY THE OCEANAIRE LIMITED WARRANTY

1 YEAR ON THE FULL PRODUCT
PLUS, 4 ADDITIONAL YEARS FOR THE COMPRESSOR
(RESTRICTIONS APPLY)

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

- OA **Cooling Capacity** is total BTUH at 80°DB/67°WB return air, 95°F Outdoor at high fan speed
- OA Dedicated Circuit and Time Delay fuses/circuit breakers are recommended
- OA EER is determined at high fan speed, with condenser discharge air ducted into another area
- OA CFM with free discharge
- OA Amps & Watts at 115 Volts

COOLING AMBIENT OPERATING RANGE 65° TO 105°

NOT APPROVED FOR OUTDOOR USE



OA-TS-2OAC1211-07262018

OCEANAIRE
OCEANAIRE-INC.COM



OCEANAIRE

TECHNICAL SPECIFICATIONS


MODEL: 2OAC1211

1 TON DELUXE SPOT COOLER

FEATURES:

- OA SOLID STATE ELECTRONIC CONTROLLER
- OA AUTOMATIC 6-SPEED FAN CONTROL WITH MANUAL OVERRIDE
- OA LARGE LED DISPLAY
- OA SWIVEL BALL BEARING CASTERS WITH LOCKS AT FRONT
- OA CONDENSATE TANK ALERT
- OA LCDI POWER CORD
- OA HIGH PRESSURE SAFETY SWITCH
- OA WASHABLE ELECTROSTATIC AIR FILTERS

ACCESSORIES



OCEANAIRE
OCEANAIRE-INC.COM

