

# OCEANAIRE

**MODEL: PAC3634**  
**3 TON SPOT COOLER**

## TECHNICAL SPECIFICATIONS

<b>COOLING CAPACITY</b>	<b>36,050 BTUH</b>
VOLTAGE	460 V, 60 Hz, Three Phase
AMPS	8.7 A
WATTS	3620 W
IN RUSH AMPS	60 A
EER	10.0
COMPRESSOR TYPE	RECIPROCATING
COMPRESSOR MOTOR	3 HP
COMPRESSOR RLA	5.0 A
COMPRESSOR LRA	35 A
EVAPORATOR BLOWER	CENTRIFUGAL
EVAP CFM - HIGH	1200
EVAP MOTOR HP	1/3 HP
CONDENSER BLOWER	CENTRIFUGAL
COND CFM	1390
COND MOTOR HP	1 HP
POWER CORD	10/4
PLUG TYPE	L16-20P
CORD LENGTH	10 FT
CONDENSATE REMOVAL SIZE	TANK 5 GALLON
REFRIGERANT CHARGE	66 OZ., R-410A
HEIGHT W/ CASTERS	50-1/4 in
HEIGHT W/O CASTERS	45 in
WIDTH	27-1/2 in
DEPTH (with 2-inch Kick Plate)	35 in
NET WEIGHT	400 lb.



**AIR COOLED**



## WARRANTY

ALL OCEANAIRE PRODUCTS ARE COVERED BY THE OCEANAIRE LIMITED WARRANTY

1 YEAR ON THE FULL PRODUCT  
PLUS, 4 ADDITIONAL YEARS FOR THE COMPRESSOR  
(RESTRICTIONS APPLY)

## SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

- OA **Cooling Capacity** is total BTUH at 80°DB/67°WB return air, 95°F Outdoor at high fan speed
- OA Dedicated Circuit and Time Delay fuses/circuit breakers are recommended
- OA EER is determined at high fan speed, with condenser discharge air ducted into another area
- OA CFM with free discharge
- OA Amps & Watts at 460 Volts

**COOLING AMBIENT OPERATING RANGE 65° TO 105°**

**NOT APPROVED FOR OUTDOOR USE**



OA-TS-PAC3634-07262018


OCEANAIRE  
OCEANAIRE-INC.COM



**MODEL: PAC3634**  
**3 TON SPOT COOLER**

### FEATURES:

- OA 24 V CONTROL CIRCUIT WITH NON-PROGRAMMABLE ELECTRONIC THERMOSTAT
- OA WASHABLE ELECTROSTATIC AIR FILTER
- OA SWIVEL BALL BEARING CASTERS WITH LOCKS AT FRONT
- OA 2-SPEED FAN SWITCH
- OA CONDENSATE TANK ALERT LIGHT
- OA HIGH PRESSURE SAFETY SWITCH
- OA THREE PHASE MONITOR



### ACCESSORIES

