

OCEANAIRE

MODEL: PWC3612

3 TON PORTABLE WATER-COOLED AC

TECHNICAL SPECIFICATIONS



WATER COOLED



WARRANTY

ALL OCEANAIRE PRODUCTS ARE COVERED BY THE OCEANAIRE LIMITED WARRANTY

1 YEAR ON THE FULL PRODUCT
PLUS, 4 ADDITIONAL YEARS FOR THE COMPRESSOR
(RESTRICTIONS APPLY)

COOLING CAPACITY

36,100 BTUH

VOLTAGE	208-230 V, 60 Hz, Single Phase
AMPS	12.0 A
WATTS	2700 W
IN RUSH AMPS	100 A
EER	13.4
COMPRESSOR TYPE	RECIPROCATING
COMPRESSOR MOTOR	3 HP
COMPRESSOR RLA	13.6 A
COMPRESSOR LRA	83 A
EVAPORATOR BLOWER	CENTRIFUGAL
EVAP CFM - HIGH	1200
EVAP MOTOR HP	1/3 HP
EVAP MOTOR AMPS	3.5 A
CONDENSER	COAXIAL
COND GPM at EWT, 60°F	2.2 GPM
COND GPM at EWT, 85°F	9.0 GPM
POWER CORD	14/3
PLUG TYPE	6-20P, LCDI
CORD LENGTH	10 FT
CONDENSATE REMOVAL LIFT (VERTICAL)	CONDENSATE PUMP 20 FT
REFRIGERANT	24 OZ., R-410A
HEIGHT W/ CASTERS	50-1/4 in
HEIGHT W/O CASTERS	45 in
WIDTH	28-1/4 in
DEPTH	18 in
NET WEIGHT	275 lb.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

- OA **Cooling Capacity** is total BTUH at 80°DB/67°WB return air, 95°F Outdoor at high fan speed
- OA Dedicated Circuit and Time Delay fuses/circuit breakers are recommended
- OA CFM with free discharge
- OA Amps & Watts at 208 Volts

COOLING AMBIENT OPERATING RANGE 65° TO 105°

NOT APPROVED FOR OUTDOOR USE



OA-TS-PWC3612-07262018

OCEANAIRE
OCEANAIRE-INC.COM



OCEANAIRE


TECHNICAL SPECIFICATIONS

MODEL: PWC 3612

3 TON PORTABLE WATER-COOLED AC



FEATURES:

- OA 24 VOLT NON-PROGRAMMABLE ELECTRONIC THERMOSTAT
- OA WASHABLE ELECTROSTATIC AIR FILTER
- OA SWIVEL BALL BEARING CASTERS WITH LOCKING FRONTS
- OA 2-SPEED FAN SWITCH
- OA AUTOMATIC WATER REGULATING VALVE
- OA INTERNAL CONDENSATE PUMP WITH OVERFLOW ALERT LIGHT
- OA LCDI POWER CORD




- **POWER CORD STORAGE AND HOSE STRAP**
- **MANUAL RESET HIGH PRESSURE CUT-OUT SWITCH**
- **RECESSED WATER CONNECTIONS**
 - **WATER IN – 5/8 FLARE**
 - **WATER OUT – 5/8 FLARE**
 - **DRAIN – 3/8 FLARE**

ACCESSORIES



5/8 HOSE KIT
HK-3 10'
HK-4 25'
HK-6 40'


**2NK-3 (2 x 8")
NOZZLE KIT**



**2DDA-16
16" DISCHARGE
DUCT ADAPTER**



**DEP-16
16" EVAPORATOR
RETURN AIR PLENUM**



OCEANAIRE
OCEANAIRE-INC.COM

