

MODEL: PWC6012

5 TON PORTABLE WATER-COOLED AC

COOLING CAPACITY 60,100 BTUH

 VOLTAGE
 208-230 V, 60 Hz, Single Phase

 AMPS
 23.7 A

 WATTS
 5000 W

 IN RUSH AMPS
 165 A

 EER
 12.0

COMPRESSOR TYPE SCROLL
COMPRESSOR MOTOR 5 HP
COMPRESSOR RLA 27.6 A
COMPRESSOR LRA 158 A

EVAPORATOR BLOWER
EVAP CFM - HIGH
EVAP MOTOR HP
EVAP MOTOR AMPS

CENTRIFUGAL
1950
1 HP
5.2A

CONDENSER COAXIAL
COND GPM at EWT, 60°F 3.8 GPM
COND GPM at EWT, 85°F 15.0 GPM
COND PRESSURE DROP 2.0 PSIG

POWER CORD 10/3
PLUG TYPE 6-30P, LCDI
CORD LENGTH 10 FT

CONDENSATE REMOVAL CONDENSATE PUMP

LIFT (VERTICAL) 20 FT

REFRIGERANT CHARGE 52 OZ., R-410A

 HEIGHT W/ CASTERS
 51-1/2 in

 HEIGHT W/O CASTERS
 45-1/4 in

 WIDTH
 27 in

 DEPTH (with 2-inch Kick Plate)
 29 in

 NET WEIGHT
 375 lb.

TECHNICAL SPECIFICATIONS





WARRANTY

ALL OCEANAIRE PRODUCTS ARE COVERED BY THE OCEANAIRE LIMITED WARRANTY

1 YEAR ON THE FULL PRODUCT PLUS, 4 ADDITIONAL YEARS FOR THE COMPRESSOR (RESTRICTIONS APPLY)

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

- OA Cooling Capacity is total BTUH at 80°DB/67°WB return air, 95°F Outdoor at high fan speed
- OA Dedicated Circuit and Time Delay fuses/circuit breakers are recommended
- OA CFM with free discharge
- Amps & Watts at 208 Volts

COOLING AMBIENT OPERATING RANGE 65° TO 105°

NOT APPROVED FOR OUTDOOR USE







OCEANAIRE


TECHNICAL SPECIFICATIONS

MODEL: PWC 6012

5 TON PORTABLE WATER-COOLED AC

FEATURES:

- OA 24 VOLT NON-PROGRAMMABLE ELECTRONIC THERMOSTAT
- **WASHABLE ELECTROSTATIC AIR FILTER**
- M SWIVEL BALL BEARING CASTERS WITH LOCKING FRONTS
- OA 2-SPEED FAN SWITCH
- OA AUTOMATIC WATER REGULATING VALVE
- OA INTERNAL CONDENSATE PUMP WITH OVERFLOW ALERT LIGHT
- OA LCDI POWER CORD



- REAR HANDLES AND KICKPLATE FOR MOBILITY
- POWER CORD STORAGE AND HOSE STRAP
- MANUAL RESET HIGH PRESSURE CUT-OUT SWITCH
- RECESSED WATER CONNECTIONS
 - WATER IN 5/8 FLARE
 - WATER OUT 5/8 FLARE
 - DRAIN 3/8 FLARE

ACCESSORIES

